



SECTION THROUGH PARKING BAY

- NOTES:
1. CONCRETE FINISH TO BE LIGHT BROOM FINISH, NEATLY TOOLED UNLESS OTHERWISE SPECIFIED.
 2. ALL BARRIER KERB IS TO BE REINSTATED WITH MWB2 KERB PROFILE (REFER TO SD1-3).
 3. CONCRETE STRENGTH OF 25MPa AT 28 DAYS.
 4. WHERE PERMISSION IS GRANTED TO USE COLOURED CONCRETE STRENGTH TO BE 32MPa.
 5. WEAKENED PLANE JOINTS LOCATED AT SPACINGS EQUAL TO THE WIDTH OF THE PARKING BAY AND MADE WITH A "T" IRON OR CONCRETE SAW CUT AS PER SD2-4.

REV	AMENDMENTS	APPROVAL	DATE
B	MINOR DRAFTING MODIFICATIONS		17-07-07
C	INCREASED CONCRETE DEPTH TO 200mm. ADDED NOTE 4		01-09-09
D	UPDATED TO REFLECT CURRENT STANDARDS	M.BRIGANDI	21-05-24

CONCRETE PARKING BAY DETAILS



45 PRINCES HIGHWAY
WERRIBEE, VIC 3030

TEL: 1300 023 411
wyndham.vic.gov.au

CAD FILE: SD11-6.DWG
DRAWN DATE: FEB 2024
REVISION: D
DRAWING NO.: SD11-6

GENERAL NOTES: -DRAWINGS ARE NOT TO SCALE.
 -ALL MEASUREMENTS ARE IN MILLIMETERS UNLESS OTHERWISE STATED.
 -FOR UP TO DATE DRAWINGS PLEASE CHECK WYNDHAM CITY COUNCIL WEBSITE.
 -ALL STANDARD DRAWINGS TO BE USED IN CONJUNCTION WITH SD1-1 (STANDARD DRAWINGS CONDITIONS OF USE).