



TYPICAL CROSS SECTION UNDER PAVEMENT

TYPICAL CROSS SECTION WITHIN ROAD RESERVE

NOTES:

1. COMPACTION TESTS TO BE UNDERTAKEN BY A NATA REGISTERED TESTER FOR SEWER AND DRAINAGE TRENCH BACKFILL, AND THE RESULTS FORWARDED TO WYNDHAM CITY COUNCIL'S CONSTRUCTION SUPERVISOR.
2. REFER TO WYNDHAM CITY COUNCIL'S GENERAL SPECIFICATION, SECTION 701, FOR DETAILS ON MATERIALS AND COMPACTION CRITERIA.
3. TRENCH WIDTH = PIPE OUTSIDE DIAMETER + 400mm.
4. IF TRENCH IS IN/THROUGH EXISTING PAVEMENT, REINSTATEMENT WIDTH OF PAVEMENT IS:
WEARING COURSE = TRENCH WIDTH + 1000mm EACH SIDE OF TRENCH.

REV	AMENDMENTS	APPROVAL	DATE
B	MINOR DRAFTING STANDARDS		06-05-07
C	UPDATED TO REFLECT CURRENT STANDARDS	M.BRIGANDI	21-05-24

CULVERT TRENCH BACKFILLING SPECIFICATIONS



45 PRINCES HIGHWAY
WERRIBEE, VIC 3030

TEL: 1300 023 411
wyndham.vic.gov.au

CAD FILE: SD6-10A.DWG

DRAWN DATE: FEB 2024

REVISION: C

DRAWING NO.:

SD6-10A

GENERAL NOTES:
 -DRAWINGS ARE NOT TO SCALE.
 -ALL MEASUREMENTS ARE IN MILLIMETERS UNLESS OTHERWISE STATED.
 -FOR UP TO DATE DRAWINGS PLEASE CHECK WYNDHAM CITY COUNCIL WEBSITE.
 -ALL STANDARD DRAWINGS TO BE USED IN CONJUNCTION WITH SD1-1 (STANDARD DRAWINGS CONDITIONS OF USE).